



Beautiful Made Easy



CRISS CROSS

SPC HERRINGBONE 5MM



*Prime Floors*TM

Unique Features



Termite
Resistant



Water Proof



Scratch
Resistant



Recyclable



Easy to
Clean Floor



Green
Product



10 years functioning
period in residences



5 years of functioning
period in commercial areas



Quick
Installation



Attached Backing
for comfort



NEW

SHB-7007

ELLE WOODS | SHB-7007



6" X 36" X 6 MM



16 Pcs/2.23 Sq.mt.

Product color may slightly vary due to photographic lighting sources or your monitor settings



NEW

SHB-7008

NATURAL COCO | SHB-7008



6" X 36" X 6 MM



16 Pcs/2.23 Sq.mt.

Product color may slightly vary due to photographic lighting sources or your monitor settings



NEW

SHB-7009

PLATINUM GREY | SHB-7009



6" X 36" X 6 MM



16 Pcs/2.23 Sq.mt.

Product color may slightly vary due to photographic lighting sources or your monitor settings



NEW
SHB-7010

CARAMEL CRUNCH | SHB-7010









6" X 36" X 6 MM



16 Pcs/2.23 Sq.mt.

Product color may slightly vary due to photographic lighting sources or your monitor settings

INSTALLATION PATTERN



SPC INSTALLATION GUIDELINES



Indoor temperature : SPC floor is suitable for indoor environment, not suitable for outdoor environment where exposed to sunlight and driving. After the floor arrives at the site, it should be left unpacked for 24-48 hours to acclimate to let the thermal expansion and contraction rate of the floor same as the new environment. The room temperature should be controlled between 18-29 degrees Celsius to avoid sun exposure before installation.



Flatness : The paving of SPC floor requires a higher level of flatness of the sub floor. Often the flatness of the sub floor directly determines whether the SPC floor can be used. Therefore, when deciding to use the SPC floor, the original ground must be leveling (terrazzo, ceramic tiles, floor paint, etc. can be laid directly), Sub floor should be flat within a tolerance of 3mm per 2 meter , otherwise, self-leveling cement should be used for leveling.



Underlayment : It is recommended to use 1.0mm underlayment, and it is forbidden to use underlayment over 2.0mm. Especially for SPC floors with a thickness of 4MM,if the sub floor uneven, underlayment too thick, which can easily cause the click to break and trip.



Allow a minimum 8-10MM gap between SPC floor and wall for spc floor expansion. If the room is particularly long and wide, the gap should be widened accordingly or T-molding should be used as partitions if the length or width greater than 10 meter. Insufficient reserved gap can easily cause floor arching and tile like deformation.



Accessories : Reducer, Quarter round, T-moulding should not prevent the floor from floating. Even no heavy furniture should be placed on the flooring as this will block the floor from expansion and contraction.



Maintenance : SPC floor does not need special maintenance, regular cleaning is enough. Avoid exposure to direct sunlight for prolonged periods of time. Do not roll or drag heavy objects across your floor. Do not polish or wax or steam clean the floor.



Product Specification

ITEM	UNIT	TEST METHODS	SPEC	PRIME FLOOR SPC
Thickness	mm	ASTM F 386	±0.005"(0.13mm)	±0.005"(0.13mm)
Size	Width	ASTM F 2055	152.4 ± 0.23	152.4 ± 0.23
	Length		914.4 ± 1.58	914.4 ± 1.58
Squareness	mm	ASTM F 2055	Max. 0.01"(0.254mm)	≤ 0.2
Gloss level	-	60° Gloss Meter		5 - 8
Size	Width	ASTM F 2199-09	≤ 0.002"(0.165%)	≤ 0.1%
	Length		≤ 0.002"(0.165%)	≤ 0.1%
Size	23°C			≤ 0.5mm
	-10°C x 2hr			≤ 0.5mm
Core Density				1.95 ± 0.05
Contraction (-10°C, 2hr)	Width	-10°C x 2hr		≤ 0.2%
	Length			≤ 0.2%
Expansion (50°C, 4hr)	Width	50°C x 4hr		≤ 0.2%
	Length			≤ 0.2%
Indentation	%	ASTM F 1914	≤ 8%	≤ 5%
Resistance to Chemicals		ASTM F 925 (Resistance to Chemicals)	No more than slight change in surface dulling, surface attack, or staining	No more than slight change in surface dulling, surface attack, or staining
IIC		ASTM F 492-09	≥50	≥52
Static Load Limit		ASTM F 970	0.005"(0.13mm)	0.005"(0.13mm)
Pieces/Box			16 pcs	16 pcs
Sq.Ft./Box			24	24
Sq.Mt./Box			2.23	2.23
CLICK			UNICLIC	UNICLIC
Box Weight			19.2 Kgs	19.2 Kgs



Beautiful Made Easy



www.excelwallpapers.com